FOODLUBE Autolube



- Premier 1FOODLUBE H1 NSF Contains •
- Accurate electromechanical grease dispenser for trouble free lubrication
 - Grease will dispense of a period set between 1-12 months
 - Ideal for hard to access areas •
- Reliable, lubricant discharge, independent of temperature and counter pressure
 - 21469 certified for full audit compliance ISO H1 registered & NSF
 - CertifiedHALAL •
 - Kosher Certified •

'??????: '?? ???? ??? **?????**

1 LE

<u> ???????? ??? ?????</u>?

???

The FOODLUBE Autolube is an electromechanical automatic lubrication system for a wide range of applications including bearings, slides and bushes within the food, pharmaceutical and other clean industries / environments.

FOODLUBE Premier 1 is an excellent high performance extreme pressure grease with PTFE. It is a soft, white, non-toxic grease ideal for fast moving bearings i.e. electric motors and fan bearings. FOODLUBE Premier 1 also has high load and wear properties, is very resistant to water washout and offers excellent corrosion protection.

The Autolube contains 120ml of grease, this can be set to dispense over a time period of 1-12 months. A pressure build up to 6 bar allows remote mounting up to 3 metres. LED lighting flashes green when in operation and red when the unit is empty.

The temperature range of the grease is -30°C to +180°C, the temperature range of the autolube unit is -10°C to +60°C.

*Food grade, electromechanical grease dispenser for trouble free lubrication

?????????

There are yet no reviews for this product.