

RT15



Perfluoropolyether based grease suitable for a wide range of applications.

- Has an excellent wide temperature range from -20°C to +280°C.
- Is an oxygen resistant, non-toxic lubricant with an extremely high oxidation and thermal resistance.
- The product has an exceptionally long service life providing excellent cost effectiveness from extended lubrication intervals, reduced downtime and reduced labour costs.
- Has outstanding extreme pressure (EP) performance with a weld load of 620 kg.
- This product is designed primarily for extreme applications in aggressive environments, however, it is also used where a long life or a lubricated for life application exists.

'?????': '?? ???? ???
?????

1 LE

[?????? ? ? ? ? ? ? ? ?](#)

???

Oxygen compatible lubricant which lengthens relubrication periods dramatically due to its ability to resist degradation in hostile conditions.

Used in gearboxes, anti-friction and plain bearings, or any sliding surface such as pins, valves, plungers, screws etc. Its resistance against aggressive chemicals and strong oxidising agents makes it a natural choice for use in the chemical, dry cleaning, food and related industries.

Extreme high load lubricant, for a wide range of aggressive environments, which will not have a detrimental effect on rubbers, plastics or metals.

*PFPE grease recommended for use in any oxygen rich environments including diving and breathing air systems such as ventilators in hospitals.

?????????

There are yet no reviews for this product.