

## SAFE STEP 200



- Ideal for use on fork-lift truck ramps and loading bays
- Two pack solvent based epoxy
- Super tough aluminium oxide aggregate for anti-slip
- Resists most acids, alkalis, solvents, grease, oil and salt water
- Usable life: 6 hours
- Available in grey
- per pack (roller applied) <sup>2</sup> Coverage: 5m
- Curing times: 24hours light traffic / 48 hours heavy traffic
- Suitable for use on concrete, wood, metal and composite surfaces
- Unaffected by extreme temperature changes when cured
- [Metal PrimerSTEP SAFE](#) or [Non-Metal PrimerSTEP SAFE](#) Designed to be applied over
- [Safe Step Hard Roller](#) Can be applied by

'?????': '?? ????? ???  
 ?????'

1 LE

[???????](#)

???

Very hard wearing even under extremely harsh conditions.

**TYPICAL APPLICATIONS**

- Factories •
- Loading bays •
- Warehouses •
- Chemical processing plants •
- Offshore oil & gas rigs •
- Stairs and fire escapes •
- Decks •
- Machine shops •

\*A superior performance, two part epoxy anti-slip coating engineered to withstand heavy vehicular and pedestrian traffic

?????????

There are yet no reviews for this product.