

SAFE STEP 500 SF



- Easy to clean and 100% solvent free
- Two pack solvent free epoxy
- content: 0 g/litre VOC
- Graded aluminium oxide aggregate for anti-slip
- Suitable for interior and exterior applications
- Ideal for use in solvent sensitive areas, e.g. breweries, food processing facilities, hospitals and confined areas
- Available in grey
- per pack (roller applied) ² Coverage: 2.7 – 4.7m
- Usable life: 30-40 minutes @ 21°C
- Curing times: 24 hours light traffic / 48 hours heavy traffic
- [Metal PrimerSTEP SAFE](#) or [Non-Metal PrimerSTEP SAFE](#) Designed to be applied over
- [Safe Step Hard Roller](#) Can be applied by

'?????': '?? ???? ???
?????

1 LE

[?????? ? ?](#)

??

Extra heavy duty, two-part epoxy anti-slip coating with integrated aggregate providing superior resistance to chemicals and wear.

TYPICAL APPLICATIONS

- Breweries •
- Food processing facilities •
- Hospitals •
- Public Areas •
- Confined areas •

*Extra heavy duty, two-part epoxy anti-slip coating with integrated aggregate providing superior resistance to chemicals and wear.

????????

There are yet no reviews for this product.