

SAPPHIRE UNILUBE



in an automatic lubricator PTFE Multi-purpose EP bearing grease fortified with

- Excellent extreme temperature resistance – ranging from -30°C to +160°C.
- , provides an outstanding high load, EP performance of 560kg that is PTFE Lithium complex soap technology and EP additives, including superior to standard soap thickened lubricants.
- Highly resistant to oxidation, providing extended lubrication intervals whilst reducing equipment failure, downtime and lubricant usage.
- Excellent corrosion resistance to protect in humid, damp and even wet conditions.
- Outstanding high speed performance for most applications found in industry.
- Advance 2 reduces stick-slip on start up ensuring a SAPHIRE has an extremely low coefficient of friction and its inclusion in PTFE smooth controlled movement.

'?????': '?? ????? ???
?????

1 LE

[?????? ? ? ? ? ? ? ? ?](#)

???

Gas operated automatic lubricator containing the high performance.

High performance bearing grease is designed for the effective lubrication and protection of all types of ball, roller and plain bearings.

Truly multi-purpose grease, fortified with PTFE, for an extensive range of applications particularly high speeds such as electric motors and fan bearings.

*Multi-purpose EP bearing grease fortified with PTFE in an automatic lubricator.

?????????

There are yet no reviews for this product.