

**OXYLUBE SPRAY** 

Page: 1

Compilation date: 23/04/2015

**Revision date:** 29/07/2019

Revision No: 8

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: OXYLUBE SPRAY

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Dry film lubricant.

### 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire LS26 8BS

**ENGLAND** 

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

### 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

### **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:

H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting

effects.

# 2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

**OXYLUBE SPRAY** 

Page: 2

GHS07: Exclamation mark GHS09: Environmental







Signal words: Danger

 $\textbf{Precautionary statements:} \quad \text{P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122}$ 

°F.

P251: Do not pierce or burn, even after use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

## 3.2. Mixtures

#### Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) - REACH registered number(s): EXEMPT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%

HYDROCARBONS C7-C9, ISOALKANES - REACH registered number(s): 01-2119471305-42

921-728-3	64741-66-8	-	Flam. Liq. 2: H225; Skin Irrit. 2: H315;	
			Aquatic Chronic 2: H411; STOT SE 3:	
			H336; Asp. Tox. 1: H304	

MOLYBDENUM DISULPHIDE - REACH registered number(s): EXEMPT UNDER ANNEX V

215-263-9	1317-33-5	Substance with a Community	-	1-10%
		workplace exposure limit.		

1-BUTANOL, TITANIUM(4+) SALT (4:1), HOMOPOLYMER

-	9022-96-2	-	Eye Irrit. 2: H319	1-10%

### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

**OXYLUBE SPRAY** 

Page: 3

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Alcohol resistant foam. Dry chemical powder.

Do not use water. Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

**OXYLUBE SPRAY** 

Page: 4

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Hazardous ingredients:**

#### HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

## Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000ppm 1750 mg/m3	1250ppm 2180 mg/m3	-	-

### **MOLYBDENUM DISULPHIDE**

UK	15mg/m3	10mg/m3	15mg/m3	10mg/m3
----	---------	---------	---------	---------

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing. **Environmental:** No data available

#### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Black

Odour: Characteristic odour

**OXYLUBE SPRAY** 

Page: 5

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Not miscible

Viscosity: Non-viscous

Boiling point/range°C: -26 Melting point/range°C: -100

Flash point°C: <21 Autoflammability°C: >200

Vapour pressure: 4270 Relative density: <1

### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

# Hazardous ingredients:

#### **HYDROCARBONS C7-C9, ISOALKANES**

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	21	mg/l

**OXYLUBE SPRAY** 

Page: 6

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

### **Section 12: Ecological information**

# 12.1. Toxicity

### Hazardous ingredients:

### **HYDROCARBONS C7-C9, ISOALKANES**

Daphnia magna	48H EC50	2.4	mg/l
Pseudokirchneriella	72H ErC50	29	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H ErC50	18.4	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Refer to local regulations for the disposal of aerosols.

**OXYLUBE SPRAY** 

Page: 7

Recovery operations: No data available

Waste code number: 16 05 05

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1950

### 14.2. UN proper shipping name

Shipping name: AEROSOLS (IATA ONLY), FLAMMABLE

### 14.3. Transport hazard class(es)

Transport class: 2.1

### 14.4. Packing group

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

## 14.6. Special precautions for user

Special precautions: No special precautions.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: No data available.

# **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: No data available

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on

the approximation of the laws of Member States relating to aerosol dispensers.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

## **OXYLUBE SPRAY**

Page: 8

H229: Pressurised container: May burst if heated.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.