



SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 1

Compilation date: 23/10/2015

Revision date: 16/01/2019

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SAFE STEP ANTI-SLIP SPRAY

Product code: 45000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Anti-Slip Floor Coating

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 2: H223; -: H229

Most important adverse effects: Flammable aerosol. Pressurised container: May burst if heated.

2.2. Label elements

Label elements:

Hazard statements: H223: Flammable aerosol.

H229: Pressurised container: May burst if heated.

Hazard pictograms: GHS02: Flame



Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

[cont...]

SAFETY DATA SHEET

SAFE STEP ANTI-SLIP SPRAY

Page: 2

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	20-30%

1-METHOXY-2-PROPANOL - REACH registered number(s): 01-2119457435-35-XXXX

203-539-1	107-98-2	-	Flam. Liq. 3: H226; STOT SE 3: H336	10-20%
-----------	----------	---	-------------------------------------	--------

XYLENE - REACH registered number(s): 01-2119488216-32-XXXX

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1.0-10%
-----------	-----------	---	---	---------

ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1.0-10%
-----------	----------	---	--	---------

TOLUENE

203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	<0.3%
-----------	----------	---	--	-------

STYRENE

202-851-5	100-42-5	-	Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319	<0.3%
-----------	----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if you feel unwell.

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIMETHYL ETHER

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m3	958 mg/m3	-	-

1-METHOXY-2-PROPANOL

UK	375 mg/m3	560 mg/m3	-	-
----	-----------	-----------	---	---

XYLENE

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

ETHYLBENZENE

UK	441 mg/m3	552 mg/m3	-	-
----	-----------	-----------	---	---

TOLUENE

UK	191 mg/m3	384 mg/m3	-	-
----	-----------	-----------	---	---

STYRENE

UK	430 mg/m3	1080 mg/m3	-	-
----	-----------	------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

XYLENE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	289	Workers	Systemic
DNEL	Dermal	180	Workers	Systemic
DNEL	Inhalation (repeated dose)	77	Workers	Systemic
DNEL	Inhalation (repeated dose)	174	Consumers	Systemic
DNEL	Inhalation (repeated dose)	174	Consumers	Local

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 5

DNEL	Dermal	108	Consumers	Local
DNEL	Inhalation	14.8	Consumers	Local
PNEC	Fresh water	0.327	-	-
PNEC	Marine water	0.327	-	-
PNEC	Microorganisms in sewage treatment	6.58	-	-
PNEC	Fresh water sediments	12.46	-	-
PNEC	Marine sediments	12.46	-	-
PNEC	Soil (agricultural)	2.31	-	-

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: No data available

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Various

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: No data available.

Solubility in water: Slightly soluble

Viscosity: No data available.

Boiling point/range°C: -22

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: -41

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.86

pH: No data available.

VOC g/l: 670

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 6

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

STYRENE

IVN	MUS	LD50	90	mg/kg
ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	2650	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

Persistence (P-):

Persistence result: not P-

Bioaccumulation (B-):

Bioaccumulation result: not B-

Toxicity (T-):

mg/l

NOEC for marine or freshwater organisms: >0.1

Toxicity result: not T-

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 8

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 08 01 11

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS (IATA ONLY), FLAMMABLE

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

[cont...]

SAFETY DATA SHEET
SAFE STEP ANTI-SLIP SPRAY

Page: 9

H223: Flammable aerosol.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H229: Pressurised container: May burst if heated.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H336: May cause drowsiness or dizziness.
H361d: Suspected of damaging the unborn child.
H372: Causes damage to organs through prolonged or repeated exposure.
H373: May cause damage to organs through prolonged or repeated exposure.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.