

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 1

Compilation date: 24/05/2015

**Revision date:** 18/05/2018

Revision No: 4

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name: SAFE STEP ASPHALT REPAIR COMPOUND

Product code: 42031

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Bitumen macadam for the repair of holes in macadam roads and paths

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: customer-service@rocol.com

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

#### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

# 2.2. Label elements

Label elements: This product has no label elements.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 2

## **Hazardous ingredients:**

#### **PAVING GRADE BITUMEN**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
232-490-9	8052-42-4	Substance with a Community	-	1.0-10%
		workplace exposure limit.		

## Non-classified ingredients:

## 1,2,4-TRIMETHYLBENZENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	<1.0%

#### **CUMENE**

202-704-5	98-82-8	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304;	
			STOT SE 3: H335; Aquatic Chronic 2:	
			H411	

## LOW BOILING POINT NAPHTHA, (PETROLEUM), (NOTE P APPLIES)

265-199-0	64742-95-6	-	Flam. Liq. 3: H226; STOT SE 3: H335;	<1.0%
			Asp. Tox. 1: H304; Aquatic Chronic 2:	
			H411; STOT SE 3: H336	

#### STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.

265-191-7   64742-88-7   -   STOT RE 1: H372; Asp. Tox. 1: H304   <1.0	.0%
--	-----

#### XYLENE - REACH registered number(s): 01-2119488216-32-XXXX

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	<1.0%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

Contains: NON-HAZARDOUS SUBSTANCE1 - 100%

# Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 3

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

# 8.1. Control parameters

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 4

#### **Hazardous ingredients:**

#### **PAVING GRADE BITUMEN**

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	10 mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Solid
Colour: Black

Odour: Characteristic odour

Relative density: >2.0

# 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 5

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

# Non-classified ingredients:

#### 1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

#### **CUMENE**

ORL	MUS	LD50	12750	mg/kg
ORL	RAT	LD50	1400	mg/kg

#### **XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Toxicity values: No data available.

# Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

# **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

# 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

# 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### SAFE STEP ASPHALT REPAIR COMPOUND

Page: 6

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national

# **Section 14: Transport information**

#### 14.1. UN number

UN number: Not Classed

## 14.2. UN proper shipping name

Shipping name: Not Classed

# 14.3. Transport hazard class(es)

## 14.4. Packing group

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

regulations regarding disposal.

# 14.6. Special precautions for user

Special precautions: No special precautions.

# **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

## SAFE STEP ASPHALT REPAIR COMPOUND

Page: 7

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.