

**ULTRACUT 550** 

Page: 1

Compilation date: 08/12/2014

Revision date: 06/01/2016

Revision No: 6

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: ULTRACUT 550

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metalworking Fluid

# 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire

LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

## 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

## **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May cause harm to breast-fed

children. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS09: Environmental



**ULTRACUT 550** 

Page: 2

Signal words: Warning

Precautionary statements: P201: Obtain special instructions before use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P263: Avoid contact during pregnancy.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P308+313: IF exposed or concerned: Get medical advice/attention.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

# **Hazardous ingredients:**

#### MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-090-8 64741-88-4		64741-88-4	Substance with a Community	-	70-90%
			workplace exposure limit.		

#### C14-C17 CHLORINATED PARAFFIN - REACH registered number(s): 01-2119519269-33-XXXX

287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410;	10-30%	
			Aquatic Acute 1: H400; -: EUH066		

# Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation: There may be coughing and a sore throat.

# 5.1. Extinguishing media

Section 5: Fire-fighting measures

**Extinguishing media:** Use water spray to cool containers. Suitable extinguishing media for the surrounding fire

should be used.

**ULTRACUT 550** 

Page: 3

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

# 6.4. Reference to other sections

# Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

#### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

**Hazardous ingredients:** 

## MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

# Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	10mg/m3	-	-

#### **DNEL/PNEC Values**

**ULTRACUT 550** 

Page: 4

## **Hazardous ingredients:**

#### C14-C17 CHLORINATED PARAFFIN

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	6.7	Workers	-
DNEL	Dermal (repeated dose)	47.9	Workers	-
DNEL	Oral	0.58	Consumers	-
DNEL	Dermal	28.75	Consumers	-
DNEL	Inhalation	2.0	Consumers	-
PNEC	Fresh water	0.001	-	-
PNEC	Marine water	0.2	-	-
PNEC	Microorganisms in sewage treatment	80	-	-
PNEC	Fresh water sediments	5	-	-
PNEC	Marine sediments	1	-	-
PNEC	Soil (agricultural)	10.5	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protection not normally required.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses with side-shields.

Skin protection: Protective clothing.

Environmental: No special requirement.

## Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Flash point°C: 200 Autoflammability°C: >300

Relative density: 0.9

## 9.2. Other information

Other information: No data available.

**ULTRACUT 550** 

Page: 5

# Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### Section 11: Toxicological information

# 11.1. Information on toxicological effects

## **Hazardous ingredients:**

#### C14-C17 CHLORINATED PARAFFIN

ORAL	RAT	LD50	> 2000	mg/kg
------	-----	------	--------	-------

Toxicity values: No data available.

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be coughing and a sore throat.

## Section 12: Ecological information

## 12.1. Toxicity

# **Hazardous ingredients:**

# C14-C17 CHLORINATED PARAFFIN

ALGAE	96H ErC50	>3.2	mg/l
Daphnia magna	48H EC50	0.006	mg/l

**ULTRACUT 550** 

Page: 6

FISH 96H LC50 >5000 mg/l

#### 12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

#### 12.4. Mobility in soil

Mobility: Non-volatile. Absorbed only slowly into soil.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

# 14.1. UN number

UN number: UN3082

#### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(C14-C17 CHLORINATED PARAFFIN)

# 14.3. Transport hazard class(es)

Transport class: 9

# 14.4. Packing group

Packing group: |||

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

# **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**ULTRACUT 550** 

Page: 7

# 15.2. Chemical Safety Assessment

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.