

**ULTRACUT EVO 280** 

Page: 1

Compilation date: 24/11/2014

**Revision date:** 29/10/2019

Revision No: 10

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: ULTRACUT EVO 280

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Water miscible metalworking fluid

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire

LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

# 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

## **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Aquatic Chronic 3: H412; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye damage. Harmful to aquatic life with long

lasting effects.

# 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

**ULTRACUT EVO 280** 

Page: 2

**Precautionary statements:** P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call POISON CENTER/doctor.

P362+P364: Take off contaminated clothing and wash it before reuse.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

# 3.2. Mixtures

### Hazardous ingredients:

ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO) - REACH registered number(s): 01-2119489407-26

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-236-9	6-9 68920-66-1 - Skin I		Skin Irrit. 2: H315; Aquatic Chronic 2:	5-10%
			H411	

## ALKENYL ALKANOL AMIDE - REACH registered number(s): 01-2119968565-22

271-653-	68603-38-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	5-10%	l
9/700-972-2			Aquatic Chronic 2: H411		l

### ALKOXYAMINE - REACH registered number(s): 01-2119488930-28

203-868-0	111-42-2	-	Acute Tox. 4: H302; Skin Irrit. 2: H315;	1-5%
			Eye Dam. 1: H318; STOT RE 2: H373	

## CARBOXYMETHYLATED POLYGLYCOL ETHER - REACH registered number(s): EXEMPT - POLYMER

-		57635-48-0	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	0.5-1%
---	--	------------	---	---------------------------------------	--------

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

[cont...]

**ULTRACUT EVO 280** 

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Alcohol or polymer foam. Alcohol resistant foam. Dry

chemical powder.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

**ULTRACUT EVO 280** 

Page: 4

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

Workplace exposure limits: No data available.

## **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Viscous

Boiling point/range°C: 100 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: > 100 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: > 200 Vapour pressure: No data available.

**Relative density:** 0.95 **pH:** No data available.

**VOC g/I:** 0

# 9.2. Other information

Other information: Not applicable.

**ULTRACUT EVO 280** 

Page: 5

# Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

# 11.1. Information on toxicological effects

# Hazardous ingredients:

## ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO)

ORAL	RAT	LD50	> 2000	ma/ka

## **ALKENYL ALKANOL AMIDE**

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>3000	mg/kg

# Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

**ULTRACUT EVO 280** 

Page: 6

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

# **Section 12: Ecological information**

# 12.1. Toxicity

### Hazardous ingredients:

### ALCOHOLS C16-C18, C18-UNSATURATED, ETHOXYLATED (<2,5 EO)

FISH	96H LC50	>1	mg/l	
1 1011	3011 LO30	-	1119/1	

### **ALKENYL ALKANOL AMIDE**

DAPHNIA	48H EC50	55	mg/l
FISH	96H LC50	1460	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

# 12.4. Mobility in soil

Mobility: No data available.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity. Harmful to aquatic organisms.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

**ULTRACUT EVO 280** 

Page: 7

## **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

## Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H373: May cause damage to organs ({{{0|||message=<or state all organs affected, if known>|||filter=(\_)?ORGAN\_.+}}}) through prolonged or repeated exposure ({{{1||| message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(\_)?EXP\_ROUTE\_.+}}}).

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.