

ULTRAGUARD BX 2000

Page: 1

Compilation date: 22/02/2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ULTRAGUARD BX 2000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Additive for water miscible metalworking fluid.

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House
	Swillington
	Leeds
	West Yorkshire
	LS26 8BS
	ENGLAND
Tel:	+44 (0) 113 232 2700
Fax:	+44 (0) 113 232 2740
Email:	customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

E.

2.1. Classification of the sub	stance or mixture
Classification under CLP:	Acute Tox. 4: H302+H312+H332; Skin Corr. 1A: H314; Skin Sens. 1: H317; STOT SE 3:
	H335; Aquatic Chronic 3: H412
Most important adverse effects:	Harmful if swallowed, in contact with skin or if inhaled Causes severe skin burns and
	eye damage. May cause an allergic skin reaction. May cause respiratory irritation.
	Harmful to aquatic life with long lasting effects.
2.2. Label elements	
Label elements:	
Hazard statements:	H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled
	H314: Causes severe skin burns and eye damage.
	H317: May cause an allergic skin reaction.
	H335: May cause respiratory irritation.
	H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

ULTRAGUARD BX 2000

Page: 2



Signal words:DangerPrecautionary statements:P280: Wear protective gloves/protective clothing/eye protection/face protection.P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomitingP302+P352: IF ON SKIN: Wash with plenty of soap and water.P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing.P501: Dispose of contents/container to local/national guidelines.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-METHYLPENTANE-1,5-DIAMINE - REACH registered number(s): 01-2119976310-41

EINECS	CAS	PBT / WEL	CLP Classification	Percent
239-556-6	15520-10-2	-	STOT SE 3: H335; Skin Corr. 1A: H314; Eye Dam. 1: H318; Acute Tox. 4: H302; Acute Tox. 4: H312; Acute Tox. 4: H332	

1,2-BENZISOTHIAZOLIN-3-ONE

220-120-9	2634-33-5	-	Acute Tox. 4: H302; Skin Irrit. 2: H315;	5-10%
			Eye Dam. 1: H318; Skin Sens. 1:	
			H317; Aquatic Acute 1: H400	

Section 4: First aid measures

4.1. Description of first aid m	easures
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Consult a doctor.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water
	to drink immediately. Consult a doctor.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
	doctor.

ULTRAGUARD BX 2000

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Alcohol resistant foam.

Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

ULTRAGUARD BX 2000

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

1,2-BENZISOTHIAZOLIN-3-ONE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	111	Consumers	Systemic

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Impermeable gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.Environmental:No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid			
Colour:	Dark brown			
Odour:	Characteristic odour			
Evaporation rate:	Negligible			
Oxidising:	Non-oxidising (by EC criteria)			
Solubility in water:	Soluble			
Viscosity:	Non-viscous			
Boiling point/range°C:	100	Melting point/range°C:	No data available	
Flammability limits %: lower:	No data available.	upper:	No data available	
Flash point°C:	Not applicable.	Part.coeff. n-octanol/water:	No data available	
Autoflammability°C:	> 200			[cont]

ULTRAGUARD BX 2000

Page: 5

Vapour pressure: No data available.

Relative density: 0.94

pH: 11.4

VOC g/I: No data available.

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-METHYLPENTANE-1,5-DIAMINE

DUST/MIST	RAT	1H LC50	4.9	mg/l
ORAL	RAT	LD50	1690	mg/kg

1,2-BENZISOTHIAZOLIN-3-ONE

ORL	MUS	LD50	1150	mg/kg
ORL	RAT	LD50	1020	mg/kg

Relevant hazards for product:

Hazard R	oute Basis
----------	------------

ULTRAGUARD BX 2000

Acute toxicity (ac. tox. 4)	INH DRM ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment metho	ds
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Recovery operations:	Not applicable.
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

ULTRAGUARD BX 2000

Page: 7

Marine pollutant: No

Section 14: Transport information

14.1. UN number

UN number: UN3267

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(2-METHYLPENTANE-1,5-DIAMINE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: |

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled
	H312: Harmful in contact with skin.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.

ULTRAGUARD BX 2000

Page: 8

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.