

LAYOUT INK SPRAY WHITE

Page: 1 Compilation date: 27/11/2014

Revision date: 14/01/2016

Revision No: 8

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LAYOUT INK SPRAY WHITE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metal Marking Ink

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House		
	Swillington		
	Leeds		
	West Yorkshire		
	LS26 8BS		
	ENGLAND		
Tel:	+44 (0) 113 232 2700		
Fax:	+44 (0) 113 232 2740		

Email: <u>customer-service@rocol.com</u>

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Flam. Aerosol 1: H222; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066; -: H229
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol.
	Pressurised container: May burst if heated. Causes serious eye irritation. May cause
	drowsiness or dizziness.

2.2. Label elements

Label elements:		
Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.	
	H222: Extremely flammable aerosol.	
	H229: Pressurised container: May burst if heated	
	H319: Causes serious eye irritation.	
	H336: May cause drowsiness or dizziness.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	

LAYOUT INK SPRAY WHITE

Page: 2



Signal words: Danger

Precautionary statements: P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P251: Do not pierce or burn, even after use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P285: In case of inadequate ventilation wear respiratory protection.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE - REACH registered number(s): 01-2119471330-49

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	50-70%
HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) - REACH registered number(s): EXEMPT				

270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	20-50%	
-----------	------------	--	-------------------------------------	--------	--

TITANIUM DIOXIDE

-	13463-67-7	Substance with a Community	-	2.4-10%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

LAYOUT INK SPRAY WHITE

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Do not use water. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking

is forbidden.

LAYOUT INK SPRAY WHITE

7.2. Conditions for safe storage, including any incompatibilities

 Storage conditions:
 Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ACETONE

Workplace exposure limits:			Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-
HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)				
UK	1000ppm 1750mg/m3	1250ppm 2180mg/m3	-	-

TITANIUM DIOXIDE

UK	4mg/m3	-
----	--------	---

DNEL/PNEC Values

Hazardous ingredients:

ACETONE

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	186	Workers	Local
DNEL	Inhalation	2420	Workers	Local
DNEL	Oral	62	Consumers	Systemic
PNEC	Fresh water	10.6	-	-
PNEC	Marine water	1.06	-	-
PNEC	Soil (agricultural)	33.3	-	-
PNEC	-	-	-	-

TITANIUM DIOXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	10	Workers	Systemic
PNEC	Fresh water	0.127	-	-

LAYOUT INK SPRAY WHITE

Page: 5

PNEC	Marine water	1	-	-
PNEC	Fresh water sediments	1000	-	-
PNEC	Soil (agricultural)	100	-	-
PNEC	Microorganisms in sewage treatment	100	-	-

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are	
	not a source of ignition.	
Respiratory protection:	Respiratory protection not normally required for normal use in well ventilated areas.	
	Respiratory protection should be used in enclosed spaces, with poor ventilation, for extended	
	repeated use, or if workplace exposure limits may be exceeded. A dust mask with P2 particle	
	filter is recommended	
Hand protection:	Nitrile gloves.	
Eye protection:	Safety glasses with side-shields.	
Skin protection:	Protective clothing.	
Environmental:	No special requirement.	

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties			
State:	Aerosol		
Colour:	White		
Odour:	Characteristic odour		
Evaporation rate:	Fast		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Viscosity:	Non-viscous		
Boiling point/range°C:	<0	Melting point/range°C:	No data available.
Flammability limits %: lower:	1.8	upper:	9.4
Flash point°C:	-100	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	No data available.	pH:	No data available.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

LAYOUT INK SPRAY WHITE

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3	gm/kg
ORL	RAT	LD50	5800	mg/kg

TITANIUM DIOXIDE

DUST/MIST	RAT	4H LC50	>6.8	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or

mental confusion may occur.

Delayed / immediate effects: No data available.

LAYOUT INK SPRAY WHITE

Page: 7

Section 12: Ecological information 12.1. Toxicity Hazardous ingredients: ACETONE BLUEGILL (Lepomis macrochirus) LC50 8300 mg/l 12.2. Persistence and degradability Persistence and degradability: Only slightly biodegradable. 12.3. Bioaccumulative potential Bioaccumulative potential: No bioaccumulation potential. 12.4. Mobility in soil Mobility: Highly volatile. Absorbed only slowly into soil. 12.5. Results of PBT and vPvB assessment PBT identification: This product is not identified as a PBT/vPvB substance. 12.6. Other adverse effects Other adverse effects: No data available. Section 13: Disposal considerations 13.1. Waste treatment methods **Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Recovery operations: No data available Waste code number: 16 05 05 Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. **NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information 14.1. UN number UN number: UN1950 14.2. UN proper shipping name Shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

Transport class: 2.1

14.4. Packing group

Packing group: n/a

LAYOUT INK SPRAY WHITE

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No data available

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: No data available.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: No data available

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	Safety data sheet prepared in accordance with Commission Directive 2008/47/EC of 8 April
	2008 amending, for the purposes of adapting to technical progress, Council Directive
	75/324/EEC relating to aerosol dispensers
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H229: Pressurised container: May burst if heated
	H280: Contains gas under pressure; may explode if heated.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and
	shall be used only as a guide. This company shall not be held liable for any damage resulting
	from handling or from contact with the above product.