## **Technical Data**



#### Performance you can trust

#### LAYOUT INK SPRAY WHITE

Layout Ink Spray White is a specialised paint designed for the marking out of metal surfaces in Toolrooms, Machine shops etc. The thin, dry film enables clear, sharply defined lines to be scribed on most surfaces without flaking.

Layout Ink Spray White is designed for use on dark or cast surfaces.

#### **Features**

- Allows clear, sharp definitions.
- Will not chip or flake.
- Resists wash off, ie. Water mix cutting fluids.
- Easy to apply and remove.

#### **Directions for Use**

- 1. Layout Ink Spray White should be applied to a grease/dirt free surface.
- 2. Shake well, hold upright and spray from a distance of 15-25cm (6-8ins).
- 3. Allow film to dry for a minimum of 2 minutes before use. Ensure adequate ventilation.

N.B. To avoid blockage, clear spray head after use by inverting can and depressing button for 2-3 seconds until jet is cleared.

Layout Ink Spray White can be easily removed with the use of a suitable solvent - ROCOL® Flawfinder Cleaner Spray.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

#### ROCOL A division of TW Ltd











# **Technical Data**



Performance you can trust

### LAYOUT INK SPRAY WHITE

Appearance	White, dry film
Propellant	Butane/Propane
Solvent	Acetone and Isopropyl alcohol
Flash Point	<0°C
Storage	Storage temperature should be kept below 50°C.
	Storage area should be out of direct sunlight.
Pack Sizes – Part Codes	400ml - 57025

Date: Jul-09

T +44 (0) 113 232 2600 **F** +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of // Ltd









