

Performance you can trust

ULTRAFORM™ 1060

High Performance Fast Drying Cold Metal Forming Lubricant

Product Overview

- ULTRAFORM 1060 is a high performance, fast drying cold metal forming lubricant, suitable for use with a wide range of ferrous and non-ferrous metals, including a range of galvanized and zinc coated steels.
- ULTRAFORM 1060 contains extreme pressure additives which prevent metal pick up between the work piece and tool providing a cost effective route to increased production rates.
- ULTRAFORM 1060 works as a vanishing film, eliminating the need to degrease components in some circumstances.
- ULTRAFORM 1060 is made from FDA listed ingredients therefore suitable for food packaging.

Directions for Storage and Use

- ULTRAFORM 2030 PLUS may be applied by brush, drip, roller, aerospray and airless spray systems.
- Store at normal ambient temperature (5 to 30°C)
- Shelf life 1 year from manufacture.

Features and Benefits

- Vanishing film - removing the need to clean or heat degrease components once formed.
- Prevention of splitting, pick-up and scoring, resulting in minimal scrap rates.
- Minimises 'slug pulling' on thin gauge materials.
- Increases production rate with reduced lubricant usage.
- Compatibility with a wide range of materials.
- Maximises tool/die life.

Pack Sizes

For pack sizes and part codes please visit:
www.rocol.com or email: customer.service@rocol.com

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer.service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds, LS26 8BS

Registered Company No 559693 VAT No 742 0531 67
Registered Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB

ROCOL A division of *ITW* Ltd





Performance you can trust

ULTRAFORM™ 1060

High Performance Fast Drying Cold Metal Forming Lubricant

Property	Result
Appearance	Colourless Liquid
Odour	Mild
Kinematic Viscosity at 25°C	2 cSt at 25°C
Density at 20°C	0.77 g/cm ³

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 3 Date: 03-20

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer.service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds, LS26 8BS

Registered Company No 559693 VAT No 742 0531 67

Registered Office: Nexus House, Station Road, Egham, Surrey, TW20 9LB

ROCOL A division of *ITW* Ltd

