

## SAFE STEP 500 SF



- Easy to clean and 100% solvent free
- Two pack solvent free epoxy
- VOC content: 0 g/litre
- Graded aluminium oxide aggregate for anti-slip
- Suitable for interior and exterior applications
- Ideal for use in solvent sensitive areas, e.g. breweries, food processing facilities, hospitals and confined areas
- Available in grey
- Coverage: 2.7 – 4.7m<sup>2</sup> per pack (roller applied)
- Usable life: 30-40 minutes @ 21°C
- Curing times: 24 hours light traffic / 48 hours heavy traffic
- Designed to be applied over [SAFE STEP Non-Metal Primer](#) or [SAFE STEP Metal Primer](#)
- Can be applied by [Safe Step Hard Roller](#)

Rating: Not Rated Yet

**Price**

1 LE

[Ask a question about this product](#)

#### Description

Extra heavy duty, two-part epoxy anti-slip coating with integrated aggregate providing superior resistance to chemicals and wear.

#### TYPICAL APPLICATIONS

- Breweries
- Food processing facilities
- Hospitals
- Public Areas
- Confined areas

\*Extra heavy duty, two-part epoxy anti-slip coating with integrated aggregate providing superior resistance to chemicals and wear.

#### Reviews

There are yet no reviews for this product.